



Disclosure to Promote the Right To Information

Whereas the Parliament of India has set out to provide a practical regime of right to information for citizens to secure access to information under the control of public authorities, in order to promote transparency and accountability in the working of every public authority, and whereas the attached publication of the Bureau of Indian Standards is of particular interest to the public, particularly disadvantaged communities and those engaged in the pursuit of education and knowledge, the attached public safety standard is made available to promote the timely dissemination of this information in an accurate manner to the public.

“जानने का अधिकार, जीने का अधिकार”

Mazdoor Kisan Shakti Sangathan

“The Right to Information, The Right to Live”

“पुराने को छोड़ नये के तरफ”

Jawaharlal Nehru

“Step Out From the Old to the New”

IS 4411 (1967): Code for designation of semiconductor devices [LITD 5: Semiconductor and Other Electronic Components and Devices]

“ज्ञान से एक नये भारत का निर्माण”

Satyanaaranay Gangaram Pitroda

“Invent a New India Using Knowledge”



“ज्ञान एक ऐसा खजाना है जो कभी चुराया नहीं जा सकता है”

Bhartṛhari—Nītiśatakam

“Knowledge is such a treasure which cannot be stolen”



BLANK PAGE



PROTECTED BY COPYRIGHT

IS : 4411 - 1967

Indian Standard
CODE FOR DESIGNATION OF
SEMICONDUCTOR DEVICES

UDC 621.382 : 003.62



© Copyright 1968

INDIAN STANDARDS INSTITUTION
MANAK BHAVAN, 9 BAHADUR SHAH ZAFAR MARG
NEW DELHI 1

Price Rs 2.00

Original Price Rs 5.00

February 1968

Indian Standard
CODE FOR DESIGNATION OF
SEMICONDUCTOR DEVICES

Semiconductor Devices Sectional Committee, ETDC 40

Chairman

Dr B. H. WADIA Semiconductors Limited, Poona

Members

DR K. S. BALAIN Central Electronics Engineering Research Institute
(CSIR), Pilani

DR P. R. DASTIDAR Bhabha Atomic Research Centre, Trombay, Bombay
SHRI M. M. FAROOQUI (*Alternate*)

SHRI B. P. GHOSH National Test House, Calcutta

SHRI A. K. GOPALAKRISHNAN The Radio, Electronic & Television Manufacturers' Association (RETMA), Bombay

SHRI S. S. MADAN Continental Devices India Ltd, Faridabad

SHRI B. S. MURTHY **Directorate General of Defence Research & Development (Ministry of Defence)**

SHRI K. C. CHHABRA (*Alternate*)

SHRI T. V. VARADARAJAN (*Alternate*)

DR RAM PARSHAD National Physical Laboratory (CSIR), New Delhi
SHRI S. P. SURI (Alternate)

SHRI K. R. SAVOOR **Bharat Electronics Ltd, Bangalore**
SHRI C. G. SUBRAMANYAN **Directorate General of Defence Research & Develop-**
ment (Ministry of Defence)

Digitized by Google

SHRI Y. S. VENKATESWARAN Director General, ISI (*Ex-officio Member*)
Director (Elec tech)

Secretary

Spring

SHRI N. SRINIVASAN

Deputy Director (Elec tech), ISI

**INDIAN STANDARDS INSTITUTION
MANAK BHAVAN, 9 BAHADUR SHAH ZAFAR MARG
NEW DELHI 1**

Indian Standard
CODE FOR DESIGNATION OF
SEMICONDUCTOR DEVICES

0. FOREWORD

0.1 This Indian Standard was adopted by the Indian Standards Institution on 12 December 1967, after the draft finalized by the Semiconductor Devices Sectional Committee had been approved by the Electrotechnical Division Council.

0.2 The object of this standard is to provide a framework for a designation code for semiconductor devices which manufacturers of semiconductor devices may use for designating and numbering their devices and also for identifying the corresponding manufacturers' data sheet.

0.3 The manufacture of semiconductor devices has been well established in this country and the number of manufacturing units and the variety of devices being put out by them have also increased. Simultaneously, the users of semiconductor devices have also multiplied at a fast rate thus calling for a wide range of properties of semiconductor devices to be covered. The need to designate the semiconductor devices and to encode each type number and its specification is also being increasingly felt.

0.4 At present the various manufacturers are following a diversity of numbering systems. Also the users often rely upon the specifications and numbers originating in different countries. A variety of numbering systems is thus in current use and a series of cross references, equivalents, correlations, etc, have become necessary.

0.5 Designation of devices developed within the country is also to be provided for. Device development has already begun at laboratory as well as at industry levels in the country and is likely to increase, as the semiconductor devices industry has been firmly implanted in the country. Hence the question of type numbers to be used on locally originated devices also requires solution.

0.6 Each country has one accepted coding and designation system of semiconductor devices for use within the country. Considering the size, the magnitude and variety of potential market in India, unification and standardization of numbering system and adoption of a single code designation of semiconductor devices is clearly indicated.

0.7 Adoption of any one of the systems existing abroad may not be the best solution because:

- a) Some of the systems are proprietary to a country or to a company;

- b) Devices originated in India would need designation and would need approach to the individual country whose system has been adopted for registration of each of these types; and
- c) In view of the variety of systems prevalent, choice of one of these systems has to be made.

0.7.1 These considerations led the Committee responsible for the preparation of this standard to realize that proper solution would therefore be to evolve a system which could be used for devices made and used in India.

0.8 It is also realized that for commercial purposes there might be need for the manufacturers to refer or use other known systems (of Japan, Europe, USA, etc) where considered expedient. It was also realized that in the meanwhile increased usage of the proposed common system should be established.

0.9 The designation numbers derived from the code specified in this standard shall identify a specific semiconductor device and be displayed prominently on it. It shall also be included in the manufacturers' data sheet for that device and thus correlate the data sheet so numbered.

0.9.1 Attempt has been made to embody in the first half of the coding system a general notation as to the nature and classification of the device. The second half of the coding system is a running number assigned serially in order of registration.

0.10 For the purposes of allotment of code designation, the device manufacturers need only apply to a body designated for the purpose, together with the data giving the minimum essential ratings and characteristics of the device. This application will be received, codified and put on record by the body designated for this purpose.

0.10.1 The ISI Directorate General which will be the appropriate body will work out the details of this procedure.

0.10.2 It should, however, be emphasized that the procedure and the coding system are for the purpose of registration and record only and do not involve any implication of quality assurance. It is the responsibility of the user or the purchaser to ensure conformity of the device with the specified ratings and characteristics.

0.11 This standard is one of a series of Indian Standards on semiconductor devices. A list of standards so far formulated in this series is given on P 6.

1. SCOPE

1.1 This standard lays down the principles relating to the designation code for semiconductor devices.

2. TERMINOLOGY

2.0 For the purpose of this standard, the terms and definitions given in IS : 1885 (Part VII)-1965* shall apply.

3. DESIGNATION SYSTEM

3.1 The type number shall consist of a maximum of six symbols being combinations of digits and letters as detailed in **3.1.1** to **3.1.4**.

3.1.1 The first symbol shall be a numeral indicating the general category of the device.

Thus:

- 1 will indicate diode
- 2 will indicate transistor
- 3 will indicate thyristor

3.1.1.1 The basis adopted for this numbering is generally the number of leads emanating from the device less one, which is also generally equal to number of junctions in the device.

3.1.1.2 The terms, diode, transistor, thyristor, etc, cover a variety of devices within themselves. For example, diode will include tunnel diode, rectifier diode, signal diode, variable capacitance diode, etc.

3.1.2 The second symbol shall be a letter indicating the basic material from which the active portion of the device is made.

Thus:

- A will indicate Germanium
- B will indicate Silicon

3.1.2.1 Further symbols for other materials will be formulated as and when necessary.

3.1.2.2 From the user's point of view, the description of the basic material would be more important than details of construction. The description of the material would automatically indicate some limitation on the use of the device. For example, germanium could be used for temperatures up to 85°C while silicon could be used for temperatures up to 200°C. Whether the construction was alloy-junction or planar might not reveal much additional information. Hence description of material in the type designation is specified.

*Electrotechnical vocabulary: Part VII Semiconductor devices.

3.1.3 The third symbol shall be a letter indicating the power-frequency limitation of the device according to a matrix given in Fig. 1.

Thus:

The letter *E* would indicate devices having a frequency limit lying between 3 and 30 Mc/s and a power dissipation lying between 1 and 10 Watts.




FIG. 1 POWER FREQUENCY MATRIX

3.1.3.1 The frequency limit is defined as the limit specified for the major use of the device, that is, transition frequency for transistors, maximum rated frequency for rectifier diodes, etc.

3.1.3.2 The method of construction of the matrix can be easily noted from the figure. The matrix squares are occupied by the alphabet in diagonal sequence.

3.1.3.3 The levels include the upper limits specified and exclude the lower limits, that is, 0-1 power level includes 1 W also while 3 to 30 Mc/s will include 30 Mc/s but exclude 3 Mc/s.

3.1.4 The three symbols specified in **3.1.1** to **3.1.3** above shall be followed by a numeral running from 100 to 999 allotted in sequence to each applicant for new device registration within the relevant category.

3.2 Designation of Special Devices — Devices having special effects and meant for specific use may be denoted by an added symbol at the end of the code specified in 3.1.

Thus for example:

<i>H</i>	for hall effect
<i>P</i>	for photo effect
<i>L</i>	for lasing
<i>T</i>	for tunnel effect
<i>Z</i>	for zener

4. TYPICAL EXAMPLES

4.1 Typical examples describing the designation specified in this standard are given below:

- a) 1 *AK* 134 : A germanium diode in the power level of 0 to 1 W and frequency level of 300 to 1 000 Mc/s having a serial number 134.
- b) 2 *BE* 372 : A silicon transistor in the power level of 1 to 10 W and frequency level of 3 to 30 Mc/s having a serial number 372.
- c) 3 *BD* 473 : A silicon thyristor in the power level of 10 to 100 W and frequency level of 0 to 3 Mc/s having a serial number 473.

INDIAN STANDARDS ON Semiconductor Devices

IS:		Rs
1885 (Part VII)-1965	Electrotechnical vocabulary: Part VII Semiconductor devices	5.50
2032 (Part VIII)-1965	Graphical symbols used in electrotechnology: Part VIII Semiconductor devices.	2.50
3700 (Part I)-1966	Essential ratings and characteristics of semiconductor devices: Part I General	1.50
3700 (Part II)-1967	Essential ratings and characteristics of semiconductor devices: Part II Low power signal diodes	2.50
3700 (Part III)-1967	Essential ratings and characteristics of semiconductor devices: Part III Rectifier diodes	2.50
3715-1966	Letter symbols for semiconductor devices	4.50
4400 (Part I)-1967	Methods of measurements on semiconductor devices: Part I General	2.00
4400 (Part II)-1967	Methods of measurements on semiconductor devices: Part II Low power signal diodes (<i>under print</i>)	—
4411-1967	Code for designation of semiconductor devices	2.00

PUBLICATIONS OF INDIAN STANDARDS INSTITUTION

INDIAN STANDARDS

About 4500 Indian Standards, broadly classified under the following main heads, have been issued so far:

Agriculture & Food
Chemical
Civil Engineering
Consumer Products

Electrotechnical
Mechanical Engineering
Structural & Metals
Textile

Of these, the standards belonging to the Electrotechnical Group fall under the following categories:

Acoustics	Instrument Transformers and Relays
Appliances	Insulating Materials
Automobile Electrical Equipment	Insulators
Batteries	Lamps and Lamp Accessories
Conductors and Cables	Lightning Arresters
Codes of Practice	Motors and Generators
Electric Welding Equipment	Nomenclature and Symbols
Electronic Components	Power Capacitors
Electronic Equipment	Power Converters
Environmental Testing	Switchgear and Controlgear
Fans	Transformers
Flame-Proof Electrical Equipment	Winding Wires
High Voltage Techniques	Wiring Accessories
Illuminating Engineering	Unclassified
Instruments and Meters	

OTHER PUBLICATIONS

	Rs
ISI Bulletin (Published Every Month)	
Single Copy ... --	2.00
Annual Subscription ... --	15.00
Annual Reports (from 1948-49 Onwards)	2.50 to 3.00 each
Handbook of ISI Publications, 1967	5.00

Available from

INDIAN STANDARDS INSTITUTION

Headquarters

Manek Bhavan, 9 Bahadur Shah Zafar Marg, New Delhi 1

Telephones 273611-20

Telegrams Manaksantha

Branch Offices

Telegrams Manaksantha

534 Sardar Vallabhbhai Patel Road
5 Chowinghee Approach
Industrial Estate Administrative
Building, Sanatnagar
117/418 B Sarvodaya Nagar
54 General Patters Road

Bombay 7	Telephone	357027
Calcutta 13	"	23-1823
Hyderabad 18	"	39229
Kanpur	"	37695
Madras 2	"	87278